

D.R. Distribution Pty. Ltd.

A.B.N.42 055448952 A.C.N.055448952
 Phone (02) 96183842 Fax (02) 98292603
 Unit 9 No 3 Lancaster St Ingleburn NSW 2565 P.O.Box 568 Ingleburn NSW 1890
 www.drdistribution.com.au

HEATSTRIP® INDOOR RADIANT INDOOR HEATERS

Heatstrip® Indoor is a range of medium intensity electric radiant heaters for protected indoor heating applications.

Features:

- Stylish, modern, sleek, slimline design
- Effective & efficient solution for open indoor areas
- Enhanced performance with new profile
- Quiet, maintenance free operation
- Flexible mounting options
- Suitable for commercial and residential applications
- Australian made



Technical Specifications:

| MODEL | POWER (WATTS) | CURRENT (AMPS) | DIMENSIONS (mm) | WEIGHT (Kg) | LEAD LENGTH (mm) | PLUG |
|--------------|---------------|----------------|-----------------|-------------|------------------|------|
| DRDTHS 800A | 800 | 3.3 | 624 x 235 x 48 | 4 | 1000 | YES |
| DRDTHS 1200A | 1200 | 5.0 | 924 x 235 x 48 | 6 | 1000 | YES |
| DRDTHS 1800A | 1800 | 7.5 | 1384 x 235 x 48 | 8 | 1000 | YES |
| DRDTHS 2400A | 2400 | 10 | 1834 x 235 x 48 | 11 | 1000 | YES |

| | |
|------------------------|---|
| HEATER TYPE | Medium intensity electric radiant overhead heater with high surface area profiled alloy |
| OUTPUT | Refer to model code chart above |
| POWER | 230240 Volts Nominal at 50—60 Hertz, Single Phase |
| CONNECTION | 3 Core Cable 1.5mm ² |
| APPROVALS | AUSTRALIA / NZ |
| MOUNTING HEIGHT | MINIMUM 2.1 m RECOMMENDED 2.1 m to 2.4 m (For higher ceiling heights, units can be lowered using optional bracket kits) |
| MOUNTING OPTIONS | Suitable for direct ceiling, angled wall, flush ceiling and TBar ceiling mounting. Also available for suspension chain mount bracket. |
| PROTECTION RATING | IP45 Protection from water ingress from all directions |
| COUNTRY OF MANUFACTURE | Australia |

Mounting Options:

