

D.R. Distribution Pty. Ltd.

A.B.N.42 055448952 A.C.N.055448952
 Phone (02) 96183842 Fax (02) 98292603
 Unit 9 No 3 Lancaster St Ingleburn NSW 2565 P.O.Box 568 Ingleburn NSW 1890
 www.drdistribution.com.au

HEATSTRIP[®]

MAX

RADIANT OUTDOOR HEATERS

Heatstrip Max is a range of high intensity electric, infrared “Low Glow” radiant heaters for tough outdoor and indoor heating applications.



Features:

- High output radiant heat
- Unique low-glow heating technology
- Suitable for permanently exposed outdoor mounting
- Maintenance free and corrosion protected
- High strength incoloy element
- Commercial grade quality — 2 year warranty
- Multiple mounting options and applications
- Australian designed, engineered and assembled

Technical Specifications:

MODEL	POWER (WATTS)	CURRENT (AMPS)	DIMENSIONS (mm)	WEIGHT (Kg)	LEAD LENGTH (mm)	PLUG
DRDTHX 2400	2400	10	854 x 170 x 80	6	1000	YES
DRDTHX 3600	3600	15	1184 x 170 x 80	8	1000	NO

HEATER TYPE	High intensity electric radiant, infrared overhead heater with Incoloy 840 element & anodized alloy casing	
POWER	230-240 Volts Nominal at 50—60 Hertz, Single Phase	
CONNECTION	3 Core Cable 1.5mm ²	
APPROVALS	AUSTRALIA/NZ	
MOUNTING HEIGHT	MINIMUM	2.1 m
	RECOMMENDED	2.4 m to 3.0 m
	MAXIMUM	3.5 m (For higher ceiling heights, units can be lowered using chains & wires or optional bracket kits)
MOUNTING OPTIONS	Suitable for ceiling, wall, beam & chain/wire mounting. Also available for extension mount using rigid fixing poles.	
PROTECTION RATING	IPX5 Protection from water ingress from all directions	
MANUFACTURED IN	Australia	

Mounting Options:

